

DESIGN CONCRETE

PRODUCT DESCRIPTION

Coated fine mineral of great strength for interior and exterior walls and floors. It can be used in wet areas (kitchen, bathrooms, swimming pools etc).

COMPOSITION

VOC not measurable below 0.1 ppm, or less than 0.00001 %.

Coating consisting of: 95 % of mineral filler: Portland cement, lime, silica 5 % of additives and resins

CHARACTERISTICS

Granulometry from 0 to 0.5 mm

Density: about 2

Adherence on concrete: 2 to 2.5 mpa

End of setting: 4-6 hours

Weight on flat surface: 1.3 kg / m²

Packaging: 10 kg bucket

Shelf life: 1 year in original packaging

TECHNICAL DATA

Application temperature: 5-30 ° C

Drying time before treatment:

- 20 ° C 24 hours

- 25 ° C 12 hours

- 5 ° C for 48 hours

APPLICATIONS

Apply two layers of 2 mm maximum.

Apply first layer at a 90° angle with the trowel

Wait at least 1 hour between coats.

Apply second layer at a 45° angle for a smoother look

Sand the second layer to make it perfectly smooth.

DESIGN
CONCRETE

DESIGN CONCRETE SHOWROOM

20 CHEPSTOW CORNER, PEMBRIDGE VILLAS

NOTTING HILL, LONDON W2 4XE

0207 727 4083 CONTACT@DESIGN-CONCRETE.CO.UK

WWW.DESIGN-CONCRETE.CO.UK